

Standard Series Dual-Stage Line-up

1024



24 inches clearing width
9.50 ft-lbs gross torque*

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
 Left Side Chute Crank Rotation
 Manual Deflector
 Electric Start
 Friction Disc Drive
 13" x 5" Tires

S1024



24 inches clearing width
9.50 ft-lbs gross torque*

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
 ⇒ **On-Panel Chute Crank**
 ⇒ **On-Panel Deflector Control**
 Electric Start
 Friction Disc Drive
 ⇒ **LED Headlight**
 ⇒ **Free Hand™ Control**
 ⇒ **14" x 5" Tires**

S1227



⇒ **27** inches clearing width
11.50 ft-lbs gross torque*

⇒ Briggs & Stratton 1150 Snow Series™ OHV Engine, 250cc
 On-Panel Chute Crank
 On-Panel Deflector Control
 Electric Start
 Friction Disc Drive
 LED Headlight
 Free Hand™ Control
 14" x 5" Tires



Made to Last
 Steel frame, chute and notched steel auger can take on snow and ice with ease.



Proven Power
 Snow Series Engines were designed to offer optimum power in cold conditions.



Free Hand™ Control
 Continue throwing snow with one hand while freeing the other to rotate the chute or adjust the speed.



Panel-Mounted Controls
 Easily adjust the chute rotation or deflector height on-the-go with on-panel controls.



Note: Images for representation only. Product may differ from image shown
 *All power levels are stated gross torque at 2600 rpm per SAE J1940 as rated by Briggs & Stratton

Dual-Stage Line-up



Model	1024	S1024	S1227	Elite 1024	Elite 1227	Elite 1530
Part #	1696610	1696614	1696619	1696807	1696815	1696828
Clearing Width	24"	24" →	27"	24" →	27" →	30"
Engine	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 950 Snow Series™ →	Briggs & Stratton 1150 Snow Series™	Briggs & Stratton 950 Snow Series™ →	Briggs & Stratton 1150 Snow Series™ →	Briggs & Stratton 1450 Professional Series™
Gross Torque (ft- lbs)*	9.50	9.50	11.50	9.50	11.50	14.50
Displacement (cc)	208	208	250	208	250	306
Gas Tank	3.2 qt. (3.0L)	3.2 qt. (3.0L)	3.2 qt. (3.0L)	3.2 qt. (3.0L)	3.2 qt. (3.0L)	3.2 qt. (3.0L)
Drive System	Friction Disc	Friction Disc	Friction Disc →	Dual-Trigger Steering	Dual-Trigger Steering	Dual-Trigger Steering
Speeds	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse
Chute Controls	Left Side Rotation / Manual Deflector →	Dash-Mounted Rotation / Remote Deflector	Dash-Mounted Rotation / Remote Deflector	Dash-Mounted Rotation / Remote Deflector	Dash-Mounted Rotation / Remote Deflector	Dash-Mounted Rotation / Remote Deflector
Tire Size	13" x 5" →	14" x 5"	14" x 5" →	16" x 4.8"	16" x 4.8"	16" x 4.8"
Headlights	None →	LED	LED	LED	LED	LED
Skid Shoes	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible
Heated Hand Grips	No	No	No →	Yes	Yes	Yes
MAP Price (US)	\$599	\$699	\$799	\$899	\$999	\$1,199



Note: Images for representation only. Product may differ from image shown
 *All power levels are stated gross torque at 2600 rpm per SAE J1940 as rated by Briggs & Stratton